

Castle Foregate, Shrewsbury, Shropshire SY1 2EL Telephone (01743) 232200 Fax (01743) 353584 www.morrislubricants.co.uk



**LODEXOL MTL** BITUMEN FREE, TRACTION MOTOR GEARBOX LUBRICANT

Reproduced courtesy of Europhoenix

## Description

Specifically designed for the lubrication of Traction Motor gears commonly found on Diesel-Electric locomotives operating on the rail networks and heritage lines.

Lodexol MTL is a highly adhesive, water resistant lubricant incorporating a highly stable additive package to prevent corrosion and wear even under high stresses and loads. The absence of Bitumen or residual oils yields a product which requires no special handling requirements unlike previous formulations used over the last 50 years.

## Features / Benefits

- Low Odour
- No special handling requirements
- Bitumen Free
- Highly adhesive
- High shock load resistance

## **Physical Characteristics**

Appearance (Concentrate) Density @ 15°C Un-worked Penetration – IP50 NLGI Consistency Pour Point Flash Point – IP 35 Brookfield Viscosity @ 15°C Brookfield Viscosity @ 100°C







High lubricityHigh water resistance

Slightly Hazy brown, Tenacious 0.956 369 0 +10℃ > 200 ℃ 512,000 cps Spindle # 4, 10rpm 2,080 cps Spindle # 2, 100rpm

> Established 1869 Morris Lubricants is a division of Paterson Enterprises Limited Shrewsbury Registered in England No. 4930959